## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 30 September 2004 (30.09.2004)

**PCT** 

## (10) International Publication Number WO 2004/082793 A2

(51) International Patent Classification7:

B01D

(21) International Application Number:

PCT/EP2004/002922

(22) International Filing Date: 19 March 2004 (19.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0306557.0

21 March 2003 (21.03.2003) GB

(71) Applicant (for all designated States except US): SPINOX LIMITED [GB/GB]; Units 14-15, Galaxy House, New Greenham Park, Newbury, Berks RG19 6HW (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): KNIGHT, David [GB/GB]; Spinox Limited, Units 14-15, Galaxy House, New Greenham Park, Newbury, Berks RG19 6HW (GB). VOLLRATH, Friedrich, Wilhelm, Ludwig, Paul [DE/GB]; Upper Woods Farm, Islip Road, Beckley, Oxford, Oxforsdhire OX3 9TF (GB).

- (74) Agent: HARRISON, Robert; Rouse Patents, Windsor House, Cornwall Road, Harrogate HG1 2PW (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR FORMING MATERIALS



(57) Abstract: The use of a starting solution to form a plurality of filler elements in a composite material is taught in this application. The starting solution comprises a miscible solution of at least one protein and a least one further compound, the plurality of filler elements being formed from the at least one further compound. Using this starting solution, further materials imparting different properties can be incorporated into the extruded proteins. Also disclosed is a method of forming a composite material containing a plurality of filler elements. This method comprises a first step of preparing a starting solution containing at least one protein and at least one further compound and a second step of inducing the starting solution to separate into a bulk phase and a minor phase. The apparatus has a storage compartment for storing the starting mixture, the starting solution and a phase separation compartment. In the phase separation compartment, the protein and the further compound of the composite forming mixture are phase separated into a bulk material containing a plurality of filler elements.

004/082793

## WO 2004/082793 A2



ML, MR, NE, SN, TD, TG).

## Published:

without international search report and to be republished upon receipt of that report

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.